

El Paso Leadership Academy
RFP #2021-004 – Security Systems Contractor
EXHIBIT G – Cabling Guidelines and Specifications

1. MATERIALS

- a. Surveillance Cameras
 - i. All surveillance equipment shall be **Avigilon Surveillance System**
 - ii. Indoor – Fixed dome, network POE camera providing HD capability. Minimum 5 MP.
 - iii. Exterior – Outdoor IP66 protected, wide-angle fixed dome, network POE camera providing HD capability. Minimum 5 MP. Mount at 12' A.F.F. unless noted otherwise.
 - iv. Include all manufacturer required device components, software, and licenses to ensure complete operation

- b. Network Video Recorder (NVR)
 - i. All surveillance equipment shall be **Avigilon Surveillance System**
 - ii. 16 Channel POE
 - iii. Solid State Drive (SSD) not less than 256GB
 - iv. Hard Disk Drive (HDD) not less than 12 TB
 - v. Redundant power supplies shall be included on server configuration
 - vi. Include all manufacturer required device components, software, and licenses to ensure complete operation

- c. Access Control System
 - i. Multi-level access control system with expandable card access
 - ii. Door grouping and/or access area capability
 - iii. Detailed time specifications including scheduling capability, expiration, and lock-down functionality
 - iv. Card enrollment reader support
 - v. Integrate with building fire alarm as required by code
 - vi. Coordinate and install Magnetic (Mag) Locks as required by code. Each Mag Lock to have a minimum force of 600 lbs. Coordinate installation with FA contractor.
 - vii. Include all manufacturer required device components, software, and licenses to ensure complete operation

- d. Card Readers
 - i. Compatible single proximity card reader at each location identified on EXHIBIT H – Project Documents.
 - ii. Integrate with building fire alarm as required by code
 - iii. Coordinate and install Magnetic (Mag) Locks as required by code. Each Mag Lock to have a minimum force of 600 lbs. Coordinate installation with FA contractor.
 - iv. Include all manufacturer required device components, software, and licenses to ensure complete operation

- e. Intercom System
 - i. All intercom systems shall be **Aiphone**
 - ii. Hands-free intercom with door station

- f. Cable
 - i. Cat6 plenum rated cable

El Paso Leadership Academy
RFP #2021-004 – Security Systems Contractor
EXHIBIT G – Cabling Guidelines and Specifications

- g. Sleeves for Firewalls
 - i. 3M Fire Barrier putty sleeve kits, DT100, DT200 and DT400 are approved for firewall penetrations. For smoke and other penetrations EMT is acceptable.

2. GUIDELINES

- a. No cable ties or zip ties will be used. Velcro (hook and loop) required.
- b. Use of staples is strictly forbidden.
- c. Service loops of at least 10' in closet and 6' patch cords at each drop.
- d. Horizontal cable managers should be placed above and below switches and fiber optic LIU with 1U of clearance above and below.
- e. Labeling of Cat6 drop on cable jacket with permanent marker highly recommended. If this is followed, labeling should be done 6" from end of cable at both ends.
- f. Cable trays will be used where available. In the event cable tray is unavailable, J-Hooks are required.
- g. Conduits cannot be filled beyond 40% capacity. Where permissible by fire code, box eliminators can be used (MP1 by CPI or BB10 by B-Line).
- h. Contractor will provide As-Built and Record Drawings to EPLA showing cabling paths, locations (with location ID) and penetrations.
- i. When cable tray is not used J-hooks should be placed no more than 6' apart with J-Hooks appropriately sized for the number of cables that are to be installed with 50% growth capability.
- j. Penetrations not provided by Design-Builder will require sleeves (sized as needed with room for 50% growth).
- k. All penetrations need to be properly fire/smoke sealed, as required.
- l. Warranty for installation needs to be provided.